


Description

Tigris® Premium, Patented Single & Turn Cylinder 3030



Technical Features

Cylinder Level	Premier 3 & 4	Clutch Function Option	Yes - Cylinder turn can not be held to prevent key holder access. Specify CLU.
No of Pins	6	Classroom Function Option	Yes - As Clutch Option but Thumbturn will only Unlock the Door. Specify CLA.
Patent Protected Key Control Until	Premier 3 - 2032, Premier 4 - 2042	Active Block Pin Security Option	Yes: Additional Side Mounted Blocking Pin. Specify ACTIVE
Multiple Key Profiles for large and/or Complex Systems	Yes: 18	Key Material	Nickel Silver for Maximum Durability & Strength
EN1303: 2005 Security Grade	6 (Highest)	Equality Act	n/a
EN1303: 2005 Durability Grade	6 (Highest)	Fixings	M5 x 70 Retaining Screw
Kitemark Anti Manipulative Tests (inc. Anti-Bump)	Option to BS3621:2007. Specify ANTI BUMP	Dimensions	
TS007 Security Level(s)	1 & 3 Star Options. Specify 1 STAR or 3 STAR	Length A x B = C (mm)	31.5 x 31.5 = 63
Protected From	Drilling & Picking	Finishes	
Construction Keyed Option	Yes - Construction Masters Negated from Cylinder at Hand Over. Specify CON.	Finishes Available	Satin Nickel, Polished Chrome, Brass (Polished, Satin & Antique), Matt Bronze, Matt Black, Matt Gold
		Colourmatch Option	Yes - finished to match neighbouring hardware. Specify COLOURMATCH

Certification

European Norm	BS EN1303:2015
Product Classification	①⑥①B①C⑥B/C
EC Certificate of Conformity No.	n/a (No Harmonised European Norm)
Certifire No.	n/a (No Harmonised European Norm)
Declaration of Performance	n/a (No Harmonised European Norm)
Other Test Evidence	Fire Tested. EN 1634:1. 60 Minutes Timber. Reference 143145.

BIM Assist™

BC(A)R Assist™*

Guarantee

15 Years

Last Reviewed 22/04/2025

* ROI Only

For the purpose of continual product development, KCC reserves the right to change specifications without notice. Please accept all dimensions as approximate. E&OE. © KCC Group 2026.

www.thekccgroup.com

Description

Tigris® Premium, Patented Single & Turn Cylinder 3030

**Specification Text****CYLINDER LOCKS**

- Standard: To BS EN 1303
- Manufacturer: Access 2
- Product reference: KC-9510
- Type: Premium, Patented Single & Turn Cylinder
- Size: 31.5/31.5 63mm Length
- Material/ finish: [SPECIFY FINISH]
- Keying: Masterkeyed
- Additional requirements: [SPECIFY ADDITIONAL OPTIONS]

PERFORMANCE SPECIFICATION CYLINDER LOCKS

- Standard: To BS EN 1303 2015
- Minimum classification grades:
- Category of use: 1
- Durability: 6
- Door mass: 0
- Suitability for use on fire/ smoke doors: B
- Safety: 0
- Corrosion and temperature resistance: C
- Key related security: 6
- Attack resistance: B/C
- Material/ finish:[SPECIFY FINISH]
- Keying: Masterkeyed

